

MOPAR ILS/LOC Y RWY05													
RMK	INA et/and API/missed approach : RNAV1 requis/required							MAG VAR 2020 0.9°E			REF NAVAI D : -		
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec	
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-	RNAV1
INA MOPAR	IF	MOPAR	-	-	-	-	-	FL070	FL070	230	-	-	RNAV1
	TF	PT402	-	93	93.9	6.4	-	-	5000	-	-	-	RNAV1
	TF	PT432	-	164	164.4	6.5	-	-	3000	-	-	-	RNAV1
	TF	PT433	-	213	213.7	7.3	-	2000	2000	-	-	-	RNAV1
	TF	PT434	-	213	213.6	3.0	-	-	-	200	-	-	RNAV1
	TF	PT435	-	164	164.6	2.8	-	-	-	185	-	-	RNAV1
	TF	IPT05	-	74	074.6	2.7	L	2000	2000	-	-	-	RNAV1
Voir carte / See chart MOPAR ILS Y CAT 1 ou/ or LOC Y RWY 05													
APCH	-	PT407	Yes	-	-	-	-	-	-	160	-	-	RNAV1
HLDG	TF	MOPAR	-	303	303.5	16.5	L	FL070	FL070	230	-	-	RNAV1
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-	-