

PRECODING INA RNAV (GNSS ou/ou DME/DME) RWY 26

INA RNAV RWY 26												
RMK	REF NAV AID : LEQ											
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ASBAR	-	-	-	-	-	-	-	-	-	-
INA ASBAR	IF	ASBAR	-	-	-	-	-	3000	-	-	-	-
	TF	OSLID	-	011	011.9	6.9	-	2000	4000	220	-	1.0
INA OSLID	TF	OLBUS	-	346	347.7	6.0	-	2000	-	210	-	1.0
	IF	OSLID	-	-	-	-	-	2000	4000	220	-	-
INA UPMIT	TF	OLBUS	-	346	347.7	6.0	-	2000	-	210	-	1.0
	IF	UPMIT	-	-	-	-	-	2000	-	170	-	-
INA OLBUS	TF	OLBUS	-	166	167.6	3.0	-	2000	-	170	-	1.0
	IF	OLBUS	-	-	-	-	-	2000	-	210	-	-