

**LILLE LESQUIN**  
**SID RNAV RWY 08**  
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 08											
RMK	(1) FA ou/or VA acceptable						MAG VAR 2020 1.2° E			REF NAV AID : LEQ	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
<b>ABB 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	211	212.0	6.1	R	-	-	-	1.0
-	TF	OBIVA	-	230	231.4	30.0	-	-	-	-	1.0
-	TF	ABB	-	262	263.6	25.3	-	-	-	-	1.0
<b>BNE 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	211	212.0	6.1	R	-	-	-	1.0
-	TF	IBERU	-	283	283.7	25.8	-	-	-	-	1.0
-	TF	BNE	-	274	274.8	21.1	-	-	-	-	1.0
<b>CIV 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	145	146.0	6.3	R	-	-	-	1.0
-	TF	DENIN	-	133	133.9	10.9	-	-	-	-	1.0
-	TF	CIV	-	050	051.4	19.7	-	-	-	-	1.0
<b>MATIX 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	145	146.0	6.3	R	-	-	-	1.0
-	TF	DENIN	-	133	133.9	10.9	-	-	-	-	1.0
-	TF	MATIX	-	130	131.0	24.8	-	-	-	-	1.0
<b>TRACA 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	211	212.0	6.1	R	-	-	-	1.0
-	TF	IBERU	-	283	283.7	25.8	-	-	-	-	1.0
-	TF	TRACA	-	308	309.6	24.1	-	-	-	-	1.0
<b>VERMA 6R</b>											
-	CA (1)	-	-	076	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	145	146.0	6.3	R	-	-	-	1.0
-	TF	VERMA	-	178	178.7	29.8	-	-	-	-	1.0