

RNP RWY 07R													
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 1,1°W			RefNAVAID : ARE	
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
	HLDG	-	RB504	-	-	-	-	-	-	-	-	-	-
	INA RB500	IF	RB500	-	-	-	-	-	-	5000	210 MAX	-	RNP APCH
		TF	RB504	-	252°	251,2	7.5	-	-	4000	200 MAX	-	RNP APCH
		TF	RB506	-	180°	178,8	4.8	-	-	3000	185 MAX	-	RNP APCH
		TF	IB07R	-	100°	098,7	3.0	-	-	2500	185 MAX	-	RNP APCH
	INA RB504	IF	RB504	-	-	-	-	-	-	4000	200 MAX	-	RNP APCH
		TF	RB506	-	180°	178,8	4.8	-	-	3000	185 MAX	-	RNP APCH
		TF	IB07R	-	100°	098,7	3.0	-	-	2500	185 MAX	-	RNP APCH
		IF	RB502	-	-	-	-	-	-	3500	185 MAX	-	RNP APCH
	INA RB502	TF	RB506	-	100°	098,7	3.5	-	-	3000	185 MAX	-	RNP APCH
		TF	IB07R	-	100°	098,7	3.0	-	-	2500	185 MAX	-	RNP APCH
		IF	IB07R	-	-	-	-	-	-	2500	185 MAX	-	RNP APCH
		TF	FB07R	-	072°	071,1	3.1	-	-	2000	-	-	RNP APCH
	APCH	TF	RW07R	Yes	072°	071,1	5.2	-	-	-	-	-3,0° / 150	RNP APCH
		TF	RB510	Yes	072°	071,2	2.7	-	-	-	200 MAX	-	RNP APCH
		DF	RB500	-	-	-	-	L	-	3000	200 MAX	-	RNP APCH