

LORIENT LANN BIHOUE
STAR RNAV RWY 25
(Protégés pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 25											
RMK	GNSS only			MAG VAR 2020 0,7 W			REF NAVID :				
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG											
		LALMO									RNAV 1
ARE 1 M											
	IF	ARE									RNAV 1
	TF	RH423		138	137.3	15.0					RNAV 1
	TF	RH424		138	137.5	17.5			FL60		RNAV 1
	TF	RH425		163	161.8	5.0		3000	FL60		RNAV 1
	TF	LALMO		253	252.0	6.0		3000	3000		RNAV 1
LENSU 1 M											
	IF	LENSU									RNAV 1
	TF	RH425		199	198.6	7.0		3000	FL60		RNAV 1
	TF	LALMO		253	252.0	6.0		3000	3000		RNAV 1
BAGAD 1 M											
	IF	BAGAD									RNAV 1
	TF	RH425		342	341.2	17.2		3000	FL60		RNAV 1
	TF	LALMO		253	252.0	6.0		3000	3000		RNAV 1