

RNP RWY 10													
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0,0°			REF NAV AID :-		
								MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec	
HLDG	-	RINED	-	-	-	-	-	-	-	-	-	-	-
INA RINED	IF	RINED	-	-	-	-	-	-	-	-	-	-	RNP APCH
	TF	RI104	-	035	035.5	3.8	-	3000	-	-	-	-	RNP APCH
INA RIKLO	TF	IRI10	-	035	035.5	3.1	-	-	-	-	-	-	RNP APCH
	IF	RIKLO	-	-	-	-	-	-	225	-	-	-	RNP APCH
INA RILAV	TF	RI116	-	191	191.2	1.2	-	-	-	-	-	-	RNP APCH
	TF	IRI10	-	191	191.2	3.0	-	-	-	-	-	-	RNP APCH
INA RILAV	IF	RILAV	-	-	-	-	-	-	-	-	-	-	RNP APCH
	TF	IRI10	-	101	101.1	5.0	-	-	-	-	-	-	RNP APCH
APCH	IF	IRI10	-	-	-	-	-	-	-	-	-	-	RNP APCH
	TF	FRI10	-	101	101.2	4.5	-	2000	2000	-	-	-	RNP APCH
	TF	RW10	Yes	101	101.3	5.2	-	-	-	-	-3.0/15	-	RNP APCH
	TF	RI112	Yes	101	101.3	3.0	-	-	-	-	-	-	RNP APCH
	DF	RI114	-	-	-	-	L	-	1700	-	-	-	RNP APCH
	TF	RI116	-	261	261.4	9.3	-	2000	-	195	-	-	RNP APCH