

RNP RWY 28												
RMK	MAG VAR 2020 0.0°										REF NAVVAID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	ROGEK	-	-	-	-	-	-	-	-	-	-
INA ROLNU	IF	ROLNU	-	-	-	-	-	-	-	220	-	RNAV1
	TF	IRI28	-	352	351.6	5	-	2000	-	-	-	RNAV1
INA ROKIX	IF	ROKIX	-	-	-	-	-	2200	-	220	-	RNAV1
	TF	IRI28	-	212	211.6	5	-	2000	-	-	-	RNAV1
INA ROGEK	IF	ROGEK	-	-	-	-	-	3000	-	-	-	RNAV1
	TF	IRI28	-	282	281.6	5	-	2000	-	-	-	RNAV1
	IF	IRI28	-	-	-	-	-	2000	-	-	-	RNP APCH
	TF	FRI28	-	281	281.5	4.4	-	2000	2000	-	-	RNP APCH
APCH	TF	RW28	Yes	281	281.5	4.5	-	-	-	-	-3.5° / 15.0	RNP APCH
	TF	RI212	Yes	281	281.5	3.2	-	-	-	-	-	RNP APCH
	DF	ROKIX	-	-	-	-	R	2200	-	180	-	RNP APCH