

Identification Procedure		RNP RWY 20						MAG VAR 2020 0,4°E			ref NAVAID : NIL	
Leg sequence	P/T	ID	Fly Over	Direction MAG °	Direction True °	Distance (NM or min)	Turn	MMI level (FL or AMSL ft)	MAX level (FL or AMSL ft)	MAX IAS (kt)	vertical angle (°) / TCH (m)	Nav Spec
INA MAPEB	IF	MAPEB	-	-	-	-	-	3000	-	220	-	RNAV1
	TF	RM504	-	020.0	020.2	22.2	R	3000	-	-	-	RNAV1
	TF	IRM20	-	110.0	110.2	5	R	3000	-	185	-	RNAV1
INA RM504	IF	RM504	-	-	-	-	-	3000	-	-	-	RNAV1
	TF	IRM20	-	110.0	110.2	5	R	3000	-	185	-	RNAV1
INA RM502	IF	RM502	-	-	-	-	-	3000	-	220	-	RNAV1
	TF	IRM20	-	290.0	290.4	5	L	3000	-	185	-	RNAV1
	IF	IRM20	-	-	-	-	-	3000	-	-	-	RNP APCH
	TF	FRM20	-	200.0	200.4	5	-	3000	-	-	-	RNP APCH
APCH	TF	RW20	Yes	200.0	200.4	7.45	-	-	-	-	-3,5° / 15	RNP APCH
	CA	-	-	200.0	200.4	-	-	2000	-	-	-	RNP APCH
	DF	MAPEB	-	-	-	-	R	3000	-	220	-	RNP APCH
HLDG	-	MAPEB	-	-	-	-	-	-	-	-	-	