

RNP RWY 28														
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0.2°W			REF NAV AID :		
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	RNP value	
	HLDG	-	ENOKI	-	-	-	-	-	-	-	-	-	-	-
		IF	ENOKI	-	-	-	-	-	-	-	-	-	-	-
	INA ENOKI	TF	RN402	-	351.2	351.2	10.4	-	4000	-	-	-	-	1.0
		TF	IRN28	-	350	350.0	4.4	-	2000	-	-	-	-	1.0
	INA RN402	IF	RN402	-	-	-	-	-	4000	-	-	-	-	-
		TF	IRN28	-	350	350.0	4.4	-	2000	-	-	-	-	1.0
	INA RN404	IF	RN404	-	-	-	-	-	-	-	-	-	-	-
		TF	IRN28	-	211	210.9	6.0	-	2000	-	-	-	-	1.0
	INA IRN28	IF	IRN28	-	-	-	-	-	2000	-	-	-	-	-
		IF	IRN28	-	-	-	-	-	2000	-	-	-	-	-
		TF	FRN28	-	281	280.8	4.1	-	2000	2000	-	-	-	1.0
	APCH	TF	RW28	Yes	281	280.8	5.8	-	-	-	-	-3.0°/51	-	0.3
		TF	RN410	Yes	281	280.8	3.0	-	-	-	-	-	-	1.0
		DF	RN412	-	-	-	-	L	-	-	190	-	-	1.0
		TF	RN402	-	080	079.9	4.0	-	4000	-	-	-	-	1.0

↑ ↑