

RNP RW29													
RMK	Leg sequence	Path Terminat or	Waypoint identification	Fly Over	Direction MAG °	Direction True °	Distance (NM)	Turn direction	MAG VAR 2020 0.8°W			Ref NAVAID: -	
									MIN level (FL or AMSL ft)	MAX level (FL or AMSL ft)	MAX IAS (kt)	vertical angle (°) / TCH (m)	Nav Spec
INA RO405		IF	RO405	-	-	-	-	-	-	-	210	-	RNAV1
		TF	IRO29	-	19	017.8	5.0	-	-	3000	195	-	RNAV1
INA AMOPO		IF	AMOPO	-	-	-	-	-	-	-	195	-	RNAV1
		TF	RO404	-	109	107.7	4.0	-	-	-	-	-	RNAV1
INA RO404		TF	IRO29	-	199	197.8	4.0	R	-	3000	-	-	RNAV1
		IF	RO404	-	-	-	-	-	-	-	195	-	RNAV1
		TF	IRO29	-	199	197.8	4.0	-	-	3000	-	-	RNAV1
		IF	IRO29	-	-	-	-	-	-	3000	195	-	RNP APCH
APCH		TF	FRO29	-	289	287.8	4.0	-	-	3000	3000	-	RNP APCH
		TF	RW29	Yes	289	287.7	8.4	-	-	-	-	-3.0° / 15.0	RNP APCH
		TF	RO410	Yes	288	287.6	1.9	-	-	-	-	-	RNP APCH
HLDG		DF	AMOPO	-	-	-	-	R	-	3000	185	-	RNP APCH
		-	AMOPO	-	-	-	-	-	-	-	-	-	-