

PRECODING RNP RWY 35

Identification Procedure	P/T	RNP RWY 35						Turn	MAG VAR 2020		MAX IAS (kt)	vertical angle (°) / TCH (m)	Nav Spec
		ID	Fly Over	Direction MAG °	Direction True °	Distance (NM or min)	MMM level (FL or AMSL ft)		MAX level (FL or AMSL ft)				
HLDG	-	DJL	-	-	-	-	-	-	-	-	-	-	-
INA SD411	IF	SD411											RNP APCH
	TF	ISD35	84.7	86.6	5.0	2400	220						RNP APCH
INA DJL	IF	DJL				3500							RNP APCH
	TF	SD412	216	218.0	7.5		3000						RNP APCH
	TF	SD411	173	175.0	5.5								RNP APCH
	TF	ISD35	85	86.6	5.0	2400	220						RNP APCH
	IF	ISD35				2400							RNP APCH
APCH	TF	FSD35	353	355.0	5.0	2400							RNP APCH
	TF	RW35	353	355.0	5.2						-3.0° / 15		RNP APCH
	TF	SD403	353	355.0	5.4			R		230			RNP APCH
	DF	SD406						R		200			RNP APCH
	TF	ISD35		256	258.4	5.0	2400		R				RNP APCH