

RNP RWY 26													
RMK	Leg sequence	MAG VAR 2020 02,3°E						RefNAVAID :					
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
	HLDG		HR	Yes	187	190.0	T 1 min	R	5500	FL 080	150		RNAV 1/ RNP APCH
	INA HR	IF	HR	-					-	-	-		RNAV 1/ RNP APCH
		TF	SM 404	-	077	079.5	12.0	-	3300	-	-		RNAV 1/ RNP APCH
		TF	ISM 26	-	167	169.7	4.9	-	2900	-	-		RNAV 1/ RNP APCH
	APCH	IF	ISM 26	-					2900	-	-		RNP APCH
		TF	FSM 26	-	257	259.7	4.7	-	2900	-	-		RNP APCH
		TF	RW 26	Yes	257	259.6	5.5	-	-	-	-	-3,0/15	RNP APCH
		TF	SM 410	Yes	257	259.3	6.9	-	-	-	-	-	RNP APCH
		DF	HR	-				R	5500	-	-	-	RNP APCH