

STRASBOURG ENTZHEIM
PRECODING INA RNAV (GNSS) RWY 05

| Identification Procedure | | INA RNP MIRGU/LUPEN RWY 05 | | | | | | MAG VAR 2020 2.5° E | | | | |
|--------------------------|-----|----------------------------|----------|--------------------|---------------------|-------------------------|------|------------------------------|------------------------------|-----------------|------------------------------------|----------|
| Leg sequence | P/T | ID | Fly Over | Direction MAG ° | Direction True ° | Distance (NM or min) | Turn | MNM level (FL or AMSL ft) | MAX level (FL or AMSL ft) | MAX IAS (kt) | vertical angle (°) / TCH (m) | Nav Spec |
| INA MIRGU-BAKIX | IF | MIRGU | | | | | | FL150 | FL220 | 250 | | |
| | TF | STM33 | | 036 | 038.1 | 17.2 | | FL100 | FL150 | 250 | | RNAV 1 |
| | TF | BAKIX | | 036 | 038.3 | 7.1 | | 7000 | FL120 | 220 | | RNP APCH |
| | TF | LOPSU | | 086 | 088.7 | 9.5 | | 5500 | 7900 | 200 | | RNP APCH |
| INA MIRGU-STM27 | IF | MIRGU | | | | | | FL150 | FL220 | 250 | | |
| | TF | STM27 | | 049 | 051.7 | 21 | | FL090 | FL120 | 250 | | RNP APCH |
| | TF | LOPSU | | 049 | 052.0 | 10.2 | | 5500 | 7900 | 200 | | RNP APCH |
| INA LUPEN-BAKIX | IF | LUPEN | | | | | | FL150 | FL200 | 250 | | |
| | TF | ST435 | | 301 | 303.3 | 13.7 | | FL110 | FL150 | 220 | | RNP APCH |
| | TF | ST445 | | 227 | 229.7 | 13.4 | | 7000 | FL100 | 220 | | RNP APCH |
| | TF | BAKIX | | 227 | 229.5 | 7.3 | | 7000 | | 220 | | RNP APCH |
| INA LUPEN-LOPSU | IF | LUPEN | | | | | | FL150 | FL200 | 250 | | |
| | TF | ST435 | | 301 | 303.3 | 13.7 | | FL110 | FL150 | 220 | | RNP APCH |
| | TF | ST445 | | 227 | 229.7 | 13.4 | | 7000 | FL100 | 220 | | RNP APCH |
| | TF | LOPSU | | 136 | 138.4 | 6 | | 5500 | 7900 | 200 | | RNP APCH |
| HLDG | - | BAKIX | - | - | - | - | - | - | - | - | - | - |